



Model 8500

Exclusively From Your Garage Pro

R-14.8* Polyurethane Insulation

Tongue-And-Groove Panels


Lifetime Limited Warranty

www.Wayne-Dalton.com



Model 8500 shown in Colonial design

Door Construction

- Rugged design consisting of 2" thick door panel construction.
- Embossed, high tensile steel panels give the look of wood with the strength of steel.
- Two-coat, baked-on polyester finish is virtually maintenance-free. This finish also makes an excellent base if you repaint to match the existing exterior colors of your home.
- The foamed-in-place polyurethane insulation is chemically bonded to each 2" thick steel section, creating a structure with higher strength and dent resistance.
- Windload models available. 
- Heavy-gauge steel wraparound end caps trim-out door edges for better appearance, improved strength and protection of the insulation from damage.
- The polyurethane foam is CFC-11-free, so it's environmentally friendly.
- Sound-absorbing insulation makes the door operate quieter and eliminates wind-rattling.
- Hot-dipped galvanized vertical supports add strength and durability.
- SilentGlide™ nylon rollers with solid steel shafts provide years of smooth, quiet and dependable operation.
- An insulated garage door improves your energy efficiency and makes your house more green.



*Insulation values have been calculated in compliance with Dasma TDS-163 industry standards.

Model 8500 Specifications

Design

- Steel panels are embossed with a wood-grained texture giving the look of genuine wood.
- All panel designs available in white, taupe, almond and brown.

Colonial




Contemporary



Ranch



Sonoma



Colors



White



Taupe



Almond



Brown

Safety & Security

- Lifting handles reduce risk to fingers from closing door panels.

Warranty

Model 8500 offers a Lifetime Limited Warranty against cracking, splitting, rusting through or section deterioration. See dealer for complete warranty details.



Windows

- Many decorative window inserts are available to enhance the look of your garage door, which in turn enhances the look of your home. Here are just a few examples. See Series 8000 (#330448), Window style brochure (#330880), or web site for all options.



Waterton I



Stockton I



Cascade I



Stockton II



Cascade II



Williamsburg II

SEE ALL THE LOOKS AVAILABLE ON OUR GARAGE DOOR DESIGN CENTER AT www.Wayne-Dalton.com

Energy Efficiency & Noise Control

- The R-14.8* polyurethane insulation is substantially more effective than the same thickness of polystyrene insulation.
- Thermal break between outside and inside steel surfaces help interrupt energy loss.
- Bulb shaped bottom seal remains flexible even in the cold to keep out bad weather.
- The foamed-in-place insulation helps block street noise from entering into living areas that adjoin the garage.
- Snug-fitting tongue-and-groove section joints seal out wind and weather.



* Insulation values have been calculated in compliance with DASMA TSD-163 industry standards.